



VIDEO



OWABLACK

BLACK MARK STAIN REMOVER/CLEAN

Product description	Fast acting and easy to use, OWABLACK cleans and removes marks/stains from gelcoat, painted and metal surfaces due to exhaust fumes, rubbing marks etc. on hulls and decks.
Properties	<ul style="list-style-type: none"> • Double action - Cleans and degreases in one. • Quickly removes. <ul style="list-style-type: none"> - Smoke stains due to exhaust fumes. - Rubbing and tread marks. - Grease stains... • Enriched with pine oil for optimum performance on oil residue. • Fast acting. Ready to use. • Does not affect the cleaned surface.
Basic uses	<ul style="list-style-type: none"> • Exterior • Hulls, Superstructures, Decks, Anti-slip surfaces, Transoms, Exhaust pipes... • Painted, metal, gelcoat and PVC surfaces.
Technical data	<p>Composition: High performance surfactants and emulsifiers. pH: 9 ± 1. Solvent Type: Water. Specific Gravity (at 20°C): 1.0 ± 0.1. Physical State: Liquid/fluid. Flammability: Non-flammable. Shelf Life: 1 year in original unopened packaging. Container Size: 1L, 2.5L Appearance: Transparent yellow liquid. VOC: N/A</p>
Application tools	Brush, Cloth, Scrubbing Sponge, Sprayer.
Good application practice	Do not apply to surfaces in direct sunlight during the hottest hours of the day. Do not use wire brushes to scrub the surface. Protect surfaces you do not wish to treat. Always test on a small inconspicuous area first. Use appropriate protective clothing - Gloves, Goggles...
Dilutions	Do not dilute.
Application	Apply OWABLACK to the surface using a brush or sprayer. Allow to work for 5 minutes. Rub surface with a clean cloth or scrubbing sponge. Rinse with fresh clean water. Repeat process if required. TIP: For very dirty surfaces soak cloth or scrubbing sponge in OWABLACK and scrub on to surface in a circular motion. If surface is too hot, dampen with water to cool before applying OWABLACK.
Clean up	Water Note: Cloths and sponges soaked in OWABLACK should be laid out flat to dry before disposing.
Storage	Store left over product in original container Keep from freezing and high temperatures.
General information	Every care is taken to ensure that the information provided in this technical data sheet is accurate. OWATROL International is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at info@owatrol.com or the local OWATROL Agent for your country. The information above is correct at the date of issue. All other OWATROL products named in this document should be used as per label instructions and the technical data sheet.
Safety	Refer to the safety data sheet (MSDS) available at www.owatrol.com and text on the packaging. Keep out of the reach of children.
Issue date	August 2016

* Same manufacturer

Owatrol Marine
is a trademark



OWATROL INTERNATIONAL SLU
Barcelona - Spain

Find all our solutions:
www.owatrol.com

The information set out cons are purely illustrative and are not the responsibility of the manufacturer, the application of products not made under his supervision.

