



INTERIOR  
EXTERIOR



# PROSOLID STAIN

## OPAQUE ACRYLIC COATING

<b>Product description</b>	Opaque acrylic coating specially designed for factory controlled application on porous substrates.
<b>Properties</b>	<ul style="list-style-type: none"> <li>• Matt finish.</li> <li>• Excellent surface protection from UV.</li> <li>• Excellent adhesion.</li> <li>• Good film resistance - breathable finish.</li> <li>• Fast drying - rapid recoat.</li> <li>• Excellent colour retention.</li> <li>• Environment friendly - very low VOC (&lt; 5%).</li> </ul>
<b>Basic uses</b>	<ul style="list-style-type: none"> <li>• Outdoor - Indoor.</li> <li>• All new and weathered exterior woods including T1-11, Cedar, Redwood and Pressure-Treated Wood.</li> <li>• Cladding, decks, fences and furniture.</li> </ul>
<b>Technical data</b>	<p><b>Tint:</b> White, grey, chamois, brick, green, blue, cedar, chocolate.  <b>Aspect:</b> Matt.  <b>Binder:</b> Acrylic resins.  <b>Solvent:</b> Water.  <b>Specific gravity at 18°C:</b> 1.24 kg/l ± 0,04 depending on colour.  <b>Viscosity Brookfield at 23°C:</b> 4000 ± 500cPo - spindle N°3, 12T/mn.  <b>Containers:</b> 20 litre, 200 litre, 1000 litre.  <b>Shelf life:</b> 2 years in original closed container.  <b>Storage conditions:</b> Avoid frost and high temperatures.  <b>Flash point:</b> &gt;+100°C.  <b>VOC:</b> &lt; 45 g/l.</p>
<b>Recommendations</b>	<p>Apply between +10°C and +30°C.          Do not apply on hot wood.          Wood moisture must be below 19%.          Do not thin - use as is.          Stir thoroughly before and periodically during application.</p>
<b>Application tools</b>	<p>Flow coating or spraying.  <b>Note:</b> Flow coaters for application of this product should be made of stainless steel.</p>
<b>Dilution</b>	Ready to use - Do not thin.
<b>Clean-up</b>	Soap and water.
<b>Coverage</b>	<p>8 to 10 m<sup>2</sup>/l.          Recommended: 90-130 g/m<sup>2</sup>.          Coverage depends on surface condition, wood porosity and application method. To assess practical coverage a test should be carried out under the precise working conditions.</p>
<b>Drying time at 23°C</b>	<p>Dust free - about 40 minutes.          Dry to touch and handling after 3 h.          Storing and filming after 4 h.</p>
<b>Application</b>	<p>Apply one coat of PROSOLID STAIN.          Let dry 3 h at 23°C (minimum).          Apply a second coat when first coat is dry (minimum 3 h at 23°C)</p>
<b>Issue date</b>	11/12

The information set out cons are purely illustrative and are not the responsibility of the manufacturer, the application of products not made under his supervision.

