



VIDEO



BLACKBAT 2 in 1 FENDER CLEANER & BLACK MARK REMOVER

| | |
|----------------------------------|---|
| Description | BLACKBAT 2 in 1 is a fast acting cleaner for fenders, inflatables, hulls, decks etc. Easy to use BLACKBAT 2 in 1 removes tough marks and stains in just a few minutes so restoring the surface to its original condition. |
| Properties | <ul style="list-style-type: none"> • Quickly and thoroughly eliminates marks and tough stains caused by: <ul style="list-style-type: none"> - Air pollution, Bad weather, Rubbing marks from docks, Footprints.... - Exhaust stains, Grease, Tar, Salt, Sail and smoke marks • Double action – Cleans and degreases in one • Extremely powerful degreasing formula. Restores treated surface to its original condition. • Enriched with pine oil for optimum performance on oil residues. • Fast acting. Quick and easy to use. • Does not alter or damage the surface. |
| Basic uses | <ul style="list-style-type: none"> • Exterior • Fenders, Inflatables (PVC, Hypalon, Neoprene). Vinyl and artificial leather. • Hulls, Superstructures, Decks, Anti-slip surfaces, Transoms, Exhaust pipes.... • Painted, metal, gelcoat and PVC surfaces. |
| Technical data | <p>Composition: High performance surfactants and emulsifiers Solvent Type: Water Specific Gravity at 20°C (68°F): 1.0 ± 0.1 Viscosity: Liquid/Fluid. Solid Content: 19% ± 2 pH: 9 ± 1 Flash point: Not classified as flammable Container Size: 1L, 2.5L Appearance: Transparent yellow liquid Shelf Life: 1 year in original unopened packaging VOC: N/A under EU Directive 2004/42</p> |
| Application tools | <p>Brush. Cloth. Scrubbing Sponge. Sprayer.</p> |
| Good application practice | <p>Do not apply in direct sunlight or to hot surfaces. Apply between 10°C (50°F) and 30°C (86°F). Do not use wire brushes to scrub the surface. Protect surfaces you do not wish to treat. Always test on a small inconspicuous area first. Avoid prolonged contact with the substrate. Use appropriate protective clothing – Gloves, Goggles....</p> |
| Dilutions | <p>Use as is. Do not dilute.</p> |
| Application | <p>Apply BLACKBAT 2 in 1 to the surface using a brush or sprayer. Allow to work for 5 minutes. Rub surface with a clean cloth or scrubbing sponge. Rinse with fresh clean water. Repeat process if required. TIP: For very dirty surfaces soak cloth or scrubbing sponge in BLACKBAT 2 in 1 and scrub on to surface in a circular motion. If surface is too hot, dampen with water to cool before applying BLACKBAT 2 in 1.</p> |
| Clean-up | <p>Water Note: Cloths soaked in BLACKBAT 2 in 1 should be laid out flat to dry before disposing.</p> |

| | |
|----------------------------|--|
| Storage | <p>Store left over product in original container.</p> <p>Close lid tightly after use.</p> <p>Keep from freezing and high temperatures.</p> |
| General information | <p>Every care is taken to ensure that the information provided in this technical data sheet is accurate.</p> <p>Owatrol International is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at info@owatrol.com or the local Owatrol Agent for your country.</p> <p>The information above is correct at the date of issue.</p> <p>All other OWATROL products named in this document should be used as per label instructions and the technical data sheet.</p> |
| Safety | <p>Refer to the safety data sheet (MSDS) available at www.owatrol.com and text on the packaging. Keep out of the reach of children.</p> |
| Issue date | <p>December 2016</p> |

**Owatrol Marine
is a trademark**

OWATROL INTERNATIONAL SLU
 Barcelona – Spain
 Tel. +34 93 125 88 68
 Fax +34 93 106 02 13



Find all our solutions:
www.owatrol.com