



NET-TROL®

WOOD CLEANER & COLOUR RESTORER



PRODUCT DESCRIPTION

NET-TROL® is a powerful cleaner and brightener, which restores grey, weather-beaten exterior wood that is unfinished to its natural colour. Unlike bleach or chlorine-based cleaners it will not damage the wood fibres. NET-TROL® removes surface and ground in dirt while restoring a bright, vibrant look to the exterior surface.

BASIC USES

- Removal of weathered grey wood fibres from untreated wood.
- Horizontal and Vertical surfaces.
- Cladding, Fences, Decking, Garden Furniture...
- Previously coated exterior surfaces in need of cleaning.
- Other surfaces – Rust-stained Cement, Discoloured Stone, Plastic, GRP....

PROPERTIES

- Lightens and restores colour to greyed, weathered wood without bleaching
- Fast acting – Works in as little as 15 minutes.
- Cleans and removes staining caused by tannins.
- Restores lustre to plastics dulled by weathering and UV rays.
- Removes rust stains.
- Cleans discoloured stone and stained cement.
- Neutralises surfaces stripped with AQUANETT®*, PREPDECK®* or DILUNETT®*.
- Safe to use – Harmless to plants and shrubs.
- Biodegradable – Does not contain solvents or bleach.

		USAGE
		Exterior
FINISH	SIZES	
N/A	1L, 2,5L, 15L	

TECHNICAL DATA

Biodegradability	Easily Biodegradable. Certificate Number: OECD 301 F (1)
Solvent Type	Water.
Specific Gravity	At 20°C (68°F) 1.07 ±0.05
Solid Content	19% ±2%
Flash Point	Not classed as flammable
Shelf Life	18 months minimum in original unopened packaging.
VOC	Out of the scope of EC Directive 2004/42.
Application Tools	Brush, Roller, Scrubbing Brush
Dilution	Removal of Grey Weathered Wood: Use undiluted. General Cleaning: Dilute up to 1 part NET-TROL® to 4 parts water, depending on the condition of the surface to be cleaned. Neutralisation: AQUANETT®*, PREPDECK®*, DILUNETT®* Use undiluted.
Coverage	5m ² (53ft ²) to 10m ² (107ft ²) per litre. Actual coverage will vary depending on application method, type, texture, age, and porosity of the surface.

Drying Times	At 20°C (68°F) and 50% RH.
	Wood – Allow to dry 2-3 days or until it meets the moisture content required by the chosen finish.
	Stone & Concrete – Allow to dry until it meets the moisture content required by the chosen finish.
Clean-up	Water
Storage	Close lid tightly after use and store in original container.
	Do not store in metal containers.
	Keep from freezing and high temperatures.

GOOD APPLICATION PRACTICE

Wear chemical resistant gloves, safety goggles and protective clothing.
 Cover everything you do not wish to coat, including plants and shrubs.
 Apply between 5°C (41°F) and 35°C (95°F).
 Do not apply in direct sunlight or to hot surfaces.
 When cleaning vertical surfaces, work from bottom to top to avoid streaking.
DO Not use a wire brush.

SURFACE PREPARATION

Remove any loose debris and surface growth e.g., moss.
 Treat mildew with a 50/50 bleach/water solution. Scrub solution on to the surface and allow to stand for 10-15 minutes; rinse thoroughly.

APPLICATION

Stir or shake can well before and during application.
 Use neat or diluted. See "Dilution" above.
 Work large areas in zones.

Wood, Stone, Concrete:

Wet surface with fresh, clean water. Apply NET-TROL®.
 Scrub surface to agitate the NET-TROL®.
 Leave to stand for approx. 10-20 minutes. If surface starts to dry, dampen with a mist application of water. Scrub surface while flushing with water or use a pressure washer (max. 60 bar/870 psi).
 Rinse thoroughly with fresh clean water. If required repeat procedure.

Nail Stains:

Clean surface. After cleaning wet surface with fresh clean water.
 Apply NET-TROL® to the entire surface over and around the nail stain. Rinse with fresh clean water **but not** until the stain has disappeared.

Plastic or GRP:

Wet surface with fresh clean water. Apply NET-TROL®.
 Leave to work for 10 minutes.
 Scrub surface with a soft or medium scrubbing brush.
 Rinse with large amounts of fresh clean water.

Rust Stains:

Wet surface with fresh clean water.
 Apply NET-TROL® with a stiff scrubbing brush working in to rust stain. Leave to work for 10 minutes.
 Re-scrub surface with a stiff scrubbing brush.
 Rinse with large amounts of fresh clean water.

Neutralising:

Apply NET-TROL® to the wet surface.
 Wood - Allow to work until wood has brightened but for at least 15 minutes.
 Other Porous Surfaces (Stone, Concrete....) - Allow to work for at least 15 minutes. Thoroughly rinse off with fresh clean water.

CAUTION:

Surfaces may be slippery when wet. Use caution when walking on wet surfaces during application.
 NET-TROL® may dull painted surfaces and some metal fixings if left on too long. Rinse off quickly or wipe with a wet cloth.

RESTRICTIONS

Do not use on Aluminium.

SAFETY

Refer to the safety data sheet (SDS) available at www.owatrol.com and the text on the label. Keep out of the reach of children.

*Same Manufacturer. *Refer to the TDS

This Technical Data sheet cancels and replaces any previous Technical Data sheet for the same product. Its purpose is to inform the user about the product. The information contained within this Technical Data sheet is based on our current knowledge. However, the information contained within this document cannot replace a specification appropriate to the nature and conditions of the substrate to be coated. Due to ongoing technical advances, it is the responsibility of the user to establish that this document has not been superseded by a more recent edition. The information contained within this document is for guidance only and the manufacturer is unable to guarantee or accept responsibility for the results as it has no control over the conditions under which its products are applied.

Publication Date: February 2023

DURIEU S.A. - 91070 Bondoufle - France
Tél +33 (0)1 60 86 48 70
Fax +33 (0)1 60 86 84 84

OWATROL INTERNATIONAL S.L.U
08007 Barcelona - Spain
Tel. +34 93 125 88 68

Owatrol®
is a trademark



Discover all our solutions at
www.owatrol.com

Our technical department is at your disposal to
answer any questions you may have at
info@owatrol.com